















USF

Access Control

## Fingerprint Time Attendance and Access Control

## Storage Capacity

10,000
10,000
10,000
10,000
1,50,000



#### **Fetures**

High-Speed and Accurate Fingerprint Identification

WIFI, TCP/IP, USB

15.56MHz Mitare (Optional)

Fingerprint, Card, Password authentication

output relay for door open.

Supremely low Electric energy consumption.

Highly reliable and durable.

Comprehensive software development kit(SDK) is available for development and integration.

### Communication Interface

Communication

Biometric	
Push Data	YES
Sensor type	500 DPI
FAR	0.00001%
FRR	0.001%
CPU	1 GHz
Verification Time	<=1 second
RF card options	125kHz EM (Standard) /
	17 5 (1411 14:5 (0 1: 1)



High-Speed and Accurate Fingerprint Identification



WiFi, TCP/IP, USB



Unaffected by High Temperatures 0° ~ 50°

### Audio/Visual

Display	Capacitive Touch Screen
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English

Software

Desktop, Web, Cloud



Time Attendance



Access Control



Employee Self Service



Mobile App

# Access control

Wiegand in & out	YES
Relay	YES
Anti Passback	YES
Standard Access Control Function	255 Time Zone, Anti-passback
	Multi-identification Verify mode

#### Power & Environment

Operating Temperature	0°c ~ 50°c
Power	12V DC / 2A
Dimension	190 x 82 x30 Pixels