



# N-BM300 W

## SIZE MATTERS



Finger



RFID



WiFi



LAN



USB



Access Control

## Fingerprint Time Attendance and Access Control

### Storage Capacity

Finger Capacity	3000
Card Capacity	3000
Max User	3000
Password	3000
Log Capacity	1,50,000



### Features

High-Speed and Accurate Fingerprint Identification

Fingerprint, Card, Password authentication

output relay for door open.

Good adaptation for dry, moist and rough fingerprints.

Supremely low Electric energy consumption.

Highly reliable and durable.

Comprehensive software development kit(SDK) is available for development and integration.

### Communication Interface

Communication	WiFi, TCP/IP, USB
---------------	-------------------

### Biometric

Push Data	YES (Optional)
Sensor type	500 DPI
FAR	0.00001%
FRR	0.001%
CPU	Industrial High Speed CPU
Verification Time	<=1 second
RF card options	125kHz EM (Standard) / 13.56MHz Mifare (Optional)



Accepts moist and rough Finger



Accepts Color & Mahendi Finger



WiFi, TCP/IP,USB



Unaffected by High  
Temperatures 0° ~ 50°

### Audio/Visual

Display	Capacitive Touch Screen
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English

Software

Desktop, Web, Cloud

### Access control

Wiegand in & out	YES
Relay	YES
Support Exit Reader	Wiegand Reader, Remote, Push Button, No Touch
Standard Access Control Function	255 Time Zone, Anti-passback Multi-identification Verify mode



Time Attendance



Access Control



Employee Self Service



Mobile App

### Power & Environment

Operating Temperature	0°c ~ 50°c
Power	12V DC / 2A
Dimension	113.0 x 113.5 x 30.0 Pixels

**Disclaimer :** Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.